

**Town of Sahuarita**

**AMENDMENTS TO THE  
INTERNATIONAL ENERGY CONSERVATION CODE  
2006 EDITION**

*The following provisions of the International Energy Conservation Code, 2006 Edition, as published by the International Code Council, Inc. are hereby revised as follows:*

**Section 101.1** *Revise as follows:*

*Insert "The Town of Sahuarita" as the jurisdiction.*

**Section 102.2** *Revise as follows:*

*After the first sentence, add "The insulation shall be installed with no gaps, no voids, no compression and no air intrusion and in complete contact with the structure's air barrier."*

**Section 503.2.7.1.1 Duct construction.** *Add the following at the end of the paragraph: "All low pressure ducts shall be leak tested in accordance with this standard. The tested rate of air leakage is not to exceed 3% of conditioned floor area in CFM at 25 Pascals (0.1 inches WC) prior to drywall and air handling equipment installation. A representative of the developer and/or builder will perform a field inspection and leakage test of the ductwork before drywall installation. The field representative will certify successful completion of this test.*

**Section 504.6 Hot water system controls.** *Revise as follows:*

*Change "to be conveniently turned off automatically or manually when the hot water system is not in operation." to read: "to be turned off automatically."*

**Section 505.6.2 Exterior lighting power.** *Revise as follows:*

*After the first sentence, add "The lighting power densities shall not exceed the allowable limits of lighting established in the Sahuarita Outdoor Lighting Code."*